

※NOTES※

MECHANICAL

- ① HOUSING : HIGH-TEMPERATURE P.B.T. UL94V-0 BLACK
- ② BUTTON : HIGH-TEMPERATURE P.B.T. UL94V-0 BLACK
- ③ COAT : BRASS, NICKEL PLATED
- ④ CONTACT FOOT : BRASS, GOLD PLATED




SPECIFICATION

- ① RATING : 50mA, 12VDC
- ② CONTACT RESISTANCE : 100mΩ MAX.
- ③ INSULATION RESISTANCE : 100MΩ MIN.
- ④ DIELECTRIC WITHSTAND VOLTAGE : 250V AC 50/60Hz FOR 1 MINUTE
- ⑤ LIFE EXPECTANCE : 100,000 CYCLES
- ⑥ OPERATING TEMPERATURE : -35°C TO +85°C
- ⑦ SOLDERABILITY PER EIA-364-52 CLASS II, CATEGORY 1



※※ THIS IS A RoHS COMPLIANT PRODUCT.

PRODUCT ORDER OPTION

PART NO.	DIM.H
SWA70-610P003N1	4.0
SWA71-610P003N1	4.8
SWA73-610P003N1	5.4
SWA74-610P003N1	6.5
SWA77-610P003N1	8.2
SWA79-610P003N1	9.5



RECOMMENDED P.C.B. LAYOUT



SCHEMATIC

QUALITY CONTROL DIMENSIONS SHALL MARKED THE SYMBOL AS RoHS COMPLIANT HIF COMPLIANT LEAD FREE	METRIC	WIROS Electronics Int'l CO., Ltd.	
	DRAWER Y. TOMITA	NOTICE OF PROPRIETARY PROPERTY: THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO WIROS ELECTRONICS INTERNATIONAL COMPANY LIMITED. AND SHOULD NOT BE USED WITHOUT WIROS'S WRITTEN CONSENT.	
	APPROVER TAI, YU	DIMENSIONS ARE IN MILLIMETERS TOLERANCES	
	ALL ±0.20 ANGULAR ±1.5°	TITLE TACTILE BUTTON SWITCH 3P THT	
DO NOT SCALE DRAWINGS			
SIZE A4	THIRD ANGLE PROJECTION	PRODUCT NUMBER SWA7*-610P003N1	SCALE 5 : 1
	REV.	SHEET 1 OF 1	